LYN 50.21
Back counter

Type 5460-5462

50 Kg self-contained ice maker
Paddle system

Lynx Series

Hollow cube
Paddle system

The Lynx series combines efficiency, speed and advanced technology to guarantee consistent performance even with particularly hard water.
The distinctive hollow structure of the cube, obtained through a paddle system with evaporator fingers, provides a large heat-exchange surface for rapid and effective cooling of the drinks.

Thanks to the natural refrigerant R290, Lynx ensures quiet operation, energy efficiency and reduced environmental impact.
Manufactured in stainless steel and ideal for built-in installation, Lynx integrates an electronic control with self-diagnosis and dedicated cleaning cycles, for precise, hygienic and consistently professional management operation.

Fields of application

Hotels	●●●●●○
Restaurants	●●●●●○
Fast Food	●○○○○○
Bars	●●●●●○
Discos	●●○○○○
Fish markets	○○○○○○
Supermarkets	○○○○○○
Medical & SPA	○○○○○○
Industries	○○○○○○

Type of ice

Hollow cube 21 g
29 x 32,5 x 41(H) mm
35 pcs per cycle

Product



Highlights

- Hollow cube with a large cooling surface
- Solid stainless steel structure
- Sportello isolato con apertura verso l'esterno, per un accesso semplice e immediato al contenitore del ghiaccio
- Easy cleanable internal rounded surfaces
- Natural gas R290 with GWP 3
- RoHS Free
- Electronic management with self-diagnostic system
- Cleaning Cycle: sanitizes the system by recirculating water with a suitable cleaning product, without activating the compressor
- Air or water cooling system
- Tropical-class machine (+43°C), suitable for installation in extreme conditions
- Front ventilation, ideal for reduced spaces (air cooled versions only)
- Front-access air condenser filter, easily removable and cleanable

Details







Package contents

N° 1 Inlet hose
N° 2 Drain hose
N° 1 Ice scoop
N° 4 Height-adjustable feet

Options and installation kits

- Special voltages
- Water treatment

Certifications

Aristarco S.p.A.
CF/PI/VAT IT01823140262

Via del Lavoro, 30 - 31033
Castelfranco Veneto, TV - Italy

T +39 0423 425611
M info@aristarco.it

www.aristarco.it

LYN 50.21
Back counter

50 Kg self-contained ice maker
Paddle system

Type 5460-5462

Operating conditions

	Min.	Max.
Ambient temperature	10 °C / 50 °F	43 °C / 110 °F
Water temperature	5 °C / 41 °F	38 °C / 100 °F
Water hardness	5 °f / 2.8 °d	20 °f / 11,3 °d
Water inlet pressure	1 bar (14 psi)	5 bar (72 psi)
Electrical voltage	-10%	+10%

Technical features

Dimensions (WxDxH)	500x585x880 mm
Net weight	51 Kg / 112 lbs
Store capacity	21 Kg / 46 lbs
Type of ice	Hollow cube
Cooling system	A/W
Type of refrigerant	R 290
Electrical supply	230 V 50 Hz
Compressor (ASHRAE conditions)	653 W
Average power consumption	310 W
Fuse	10 A
Electrical consumption	16,40 kWh/100Kg
Water consumption	A = 5,3 l/h W = 46,2 l/h
Heat rejected	937 W
Noise level	< 70 dB

All the technical information must be considered at the following conditions:
Dimensions without feet
Standard Voltage (50 Hz)
Ambient temperature +32° C
Water temperature +21° C

Performances

Air cooled system

Room temp.	Water temp.	Prod. in 24h
10° C / 50° F	10° C / 50° F	51 Kg / 112 lbs
21° C / 70° F	**15° C / 60° F**	**46 Kg / 101 lbs**
32° C / 90° F	21° C / 70° F	38 Kg / 84 lbs

Water cooled system


Room temp.	Water temp.	Prod. in 24h
10° C / 50° F	10° C / 50° F	53 kg / 117 lbs
21° C / 70° F	**15° C / 60° F**	**50 Kg / 110 lbs**
32° C / 90° F	21° C / 70° F	45 Kg / 99 lbs

Logistic


Packing dimensions (WxDxH)	640x560x1050 mm 0,38 m3
Gross weight	58 Kg / 128 lbs

Installation diagram

Frontal view




Lateral view




*All dimensions are expressed in mm

Top view



Rear view
(Water and electrical connections)



E.I. POWER CABLE
3x1,5 mm2

D DRAIN HOSE
Ø 20 mm L=2 m

C.D. DRAIN HOSE FOR COOLING
3/4" L=1,5 m

W.I. INLET HOSE
3/4" L=1,5 m

Aristarco S.p.A.
CF/PI/VAT IT01823140262

Via del Lavoro, 30 - 31033
Castelfranco Veneto, TV - Italy

T +39 0423 425611
M info@aristarco.it

www.aristarco.it