LYN 60.28
Back counter

Type 5470-5472

60 Kg self-contained ice maker
Paddle system

Lynx Series

Hollow cube
Paddle system

The Lynx series combines efficiency, speed and advanced technology to guarantee consistent performance even with particularly hard water.
The distinctive hollow structure of the cube, obtained through a paddle system with evaporator fingers, provides a large heat-exchange surface for rapid and effective cooling of the drinks.

Thanks to the natural refrigerant R290, Lynx ensures quiet operation, energy efficiency and reduced environmental impact.
Manufactured in stainless steel and ideal for built-in installation, Lynx integrates an electronic control with self-diagnosis and dedicated cleaning cycles, for precise, hygienic and consistently professional management operation.

Fields of application

Hotels	●●●●●○
Restaurants	●●●●●○
Fast Food	●○○○○○
Bars	●●●●●○
Discos	●●○○○○
Fish markets	○○○○○○
Supermarkets	○○○○○○
Medical & SPA	○○○○○○
Industries	○○○○○○

Type of ice

Hollow cube 21 g
29 x 32,5 x 41(H) mm
35 pcs per cycle

Product



Highlights

- Hollow cube with a large cooling surface
- Solid stainless steel structure
- Sportello isolato con apertura verso l'esterno, per un accesso semplice e immediato al contenitore del ghiaccio
- Easy cleanable internal rounded surfaces
- Natural gas R290 with GWP 3
- RoHS Free
- Electronic management with self-diagnostic system
- Cleaning Cycle: sanitizes the system by recirculating water with a suitable cleaning product, without activating the compressor
- Air or water cooling system
- Tropical-class machine (+43°C), suitable for installation in extreme conditions
- Front ventilation, ideal for reduced spaces (air cooled versions only)
- Front-access air condenser filter, easily removable and cleanable

Details







Package contents

N° 1 Inlet hose
N° 2 Drain hose
N° 1 Ice scoop
N° 4 Height-adjustable feet

Options and installation kits

- Special voltages
- Water treatment

Certifications

Aristarco S.p.A.
CF/PI/VAT IT01823140262

Via del Lavoro, 30 - 31033
Castelfranco Veneto, TV - Italy

T +39 0423 425611
M info@aristarco.it

www.aristarco.it

LYN 60.28
Back counter

60 Kg self-contained ice maker
Paddle system

Type 5470-5472

Operating conditions

	Min.	Max.
Ambient temperature	10 °C / 50 °F	43 °C / 110 °F
Water temperature	5 °C / 41 °F	38 °C / 100 °F
Water hardness	5 °f / 2.8 °d	20 °f / 11,3 °d
Water inlet pressure	1 bar (14 psi)	5 bar (72 psi)
Electrical voltage	-10%	+10%

Technical features

Dimensions (WxDxH)	600x585x880 mm
Net weight	52 kg / 115 lbs
Store capacity	28 Kg / 62 lbs
Type of ice	Hollow cube
Cooling system	A/W
Type of refrigerant	R 290
Electrical supply	230 V 50 Hz
Compressor (ASHRAE conditions)	1.054 W
Average power consumption	460 W
Fuse	10 A
Electrical consumption	21,80 kWh/100Kg
Water consumption	A = 6,4 l/h W = 60,8 l/h
Heat rejected	1.537 W
Noise level	< 70 dB

All the technical information must be considered at the following conditions:
Dimensions without feet
Standard Voltage (50 Hz)
Ambient temperature +32° C
Water temperature +21° C

Performances

Air cooled system

Room temp.	Water temp.	Prod. in 24h
10° C / 50° F	10° C / 50° F	63 Kg / 139 lbs
21° C / 70° F	**15° C / 60° F**	**57 Kg / 126 lbs**
32° C / 90° F	21° C / 70° F	45 Kg / 99 lbs

Water cooled system


Room temp.	Water temp.	Prod. in 24h
10° C / 50° F	10° C / 50° F	66 kg / 146 lbs
21° C / 70° F	**15° C / 60° F**	**62 Kg / 137 lbs**
32° C / 90° F	21° C / 70° F	58 Kg / 128 lbs

Logistic


Packing dimensions (WxDxH)	660x640x1050 mm 0,45 m3
Gross weight	60 Kg / 132 lbs

Installation diagram

Frontal view




Lateral view




*All dimensions are expressed in mm

Top view



Rear view
(Water and electrical connections)



E.I. POWER CABLE
3x1,5 mm2

D DRAIN HOSE
Ø 20 mm L=2 m

C.D. DRAIN HOSE FOR COOLING
3/4" L=1,5 m

W.I. INLET HOSE
3/4" L=1,5 m

Aristarco S.p.A.
CF/PI/VAT IT01823140262

Via del Lavoro, 30 - 31033
Castelfranco Veneto, TV - Italy

T +39 0423 425611
M info@aristarco.it

www.aristarco.it