PIC 140
Modular

Type 5505-5506

140 Kg modular ice maker
Vertical evaporator system

Pictor Series

Dice cube
Vertical evaporator system

The Pictor series combines the ideal solution for QSRs (Quick Service Restaurants) and coffee shop chains. The classic six-sided solid cube, created by a high-yield vertical copper evaporator, guarantees rapid and uniform cooling of drinks, with efficiency close to 100%.

Available in three formats - Half-Dice 6g, Dice 10g and Large-Dice 17g they offer operational flexibility and reduced water consumption, thanks to the natural refrigerant R290.
Manufactured in stainless steel and ideal for built-in installation, the KQ series integrates an electronic control with self-diagnosis and dedicated cleaning cycles, combining structural robustness with precise,

Fields of application

Hotels	●●●○○○
Restaurants	●●○○○○
Fast Food	●●●●●○
Bars	●●●○○○
Discos	●●●●●○
Fish markets	○○○○○○
Supermarkets	●○○○○○
Medical & SPA	○○○○○○
Industries	●○○○○○

Type of ice

HD — Half dice cube (HD) 6 g
10 x 29 x 24(H) mm
265 pcs per cycle

D — Dice cube (D) 10 g
22 x 22 x 24(H) mm
168 pcs per cycle

LD — Large dice cube (LD) 17 g
29 x 29 x 24(H) mm
110 pcs per cycle

Product



Highlights

- Dice, Half dice or Large dice solid ice cubes for maximum cooling surface
- Solid stainless steel structure
- Easy cleanable internal rounded surfaces
- Natural gas R290 with GWP 3
- RoHS Free
- Electronic management with self-diagnostic system
- Cleaning Cycle: sanitizes the system by recirculating water with a suitable cleaning product, without activating the compressor
- Air or water cooling system
- Tropical-class machine (+43°C), suitable for installation in extreme conditions
- Dual water inlet system with twin solenoid valves for efficient water supply (water cooled model)
- Air condenser filter, easily removable and cleanable
- Easy to access for maintenance

Details







Recommended bins

- ST S 150 (130 Kg / 287 lbs), ST S 200 (180 Kg / 397 lbs)

Package contents

N° 1 Inlet hose
N° 1 Inlet hose for cooling (water-cooled versions only)
N° 1 Drain hose
N° 1 Cooling drain hose (water-cooled versions only)

Options and installation kits

- Special voltages
- Water treatment

Certifications

Aristarco S.p.A.
CF/PI/VAT IT01823140262

Via del Lavoro, 30 - 31033
Castelfranco Veneto, TV - Italy

T +39 0423 425611
M info@aristarco.it

www.aristarco.it

PIC 140
Modular

140 Kg modular ice maker
Vertical evaporator system

Type 5505-5506

Operating conditions

	Min.	Max.
Ambient temperature	10 °C / 50 °F	43 °C / 110 °F
Water temperature	5 °C / 41 °F	38 °C / 100 °F
Water hardness	5 °f / 2.8 °d	20 °f / 11,3 °d
Water inlet pressure	1 bar (14 psi)	5 bar (72 psi)
Electrical voltage	-10%	+10%

Technical features

Dimensions (WxDxH)	560x620x575 mm
Net weight	53 kg / 117 lbs
Type of ice	Dice cube
Cooling system	A/W
Type of refrigerant	R 290
Electrical supply	230 V 50 Hz
Compressor (ASHRAE conditions)	1.131 W
Average power consumption	650 W
Fuse	10 A
Electrical consumption	13,00 kWh/100Kg
Water consumption	A = 7,7 l/h W = 54,3 l/h
Heat rejected	1.781 W
Noise level	< 70 dB

All the technical information must be considered at the following conditions:
Dimensions without feet
Standard cube (10 g)
Standard Voltage (50 Hz)
Ambient temperature +32° C
Water temperature +21° C

Performances

Air cooled system

Room temp.	Water temp.	Prod. in 24h
10° C / 50° F	10° C / 50° F	155 Kg / 342 lbs
21° C / 70° F	**15° C / 60° F**	**140 Kg / 309 lbs**
32° C / 90° F	21° C / 70° F	116 Kg / 256 lbs

Water cooled system


Room temp.	Water temp.	Prod. in 24h
10° C / 50° F	10° C / 50° F	155 Kg / 342 lbs
21° C / 70° F	**15° C / 60° F**	**140 Kg / 309 lbs**
32° C / 90° F	21° C / 70° F	130 Kg / 287 lbs

Logistic


Packing dimensions (WxDxH)	690x630x740 mm 0,32 m3
Gross weight	65 Kg / 143 lbs

Installation diagram

Frontal view




Lateral view




*All dimensions are expressed in mm

Top view



Rear view
(Water and electrical connections)



E.I. POWER CABLE 3x1,5 mm2

D DRAIN HOSE Ø 20 mm L=2 m

C.D. DRAIN HOSE FOR COOLING 3/4" L=1,5 m

W.I. INLET HOSE 3/4" L=1,5 m

C.I. INLET HOSE FOR COOLING 3/4" L=1,5 m

Aristarco S.p.A.
CF/PI/VAT IT01823140262

Via del Lavoro, 30 - 31033
Castelfranco Veneto, TV - Italy

T +39 0423 425611
M info@aristarco.it

www.aristarco.it